





Approved Supplier for the NSW Government, under the Office Furniture Scheme SCM0771.



JOINER TYPES:



JOINER STRAIGHT 195 x 25 x 28mm



JOINER 90 128.2 x 128.2 x 25 x 28mm



JOINER 120 198 x 25 x 28mm



JOINER T 195 x 128 x 25 x 28mm



JOINER X 228 x 228 x 25 x 28mm



JOINER Y 198 x 198 x 25 x 28mm

PALING

Lead Time: 6 - 8 weeks Warranty: 1 Year SPEC SHEET

Please refer to a physical sample. Images are for an indicative reference only.

Actual product may vary slightly, depending upon model configurations.

Lead time subject to PET screen supplier's stock availability.

FEATURES

- » Echo Panel® 24mm
- » 100% PET (60% recycled)
- » Low VOC
- » Global GreenTAG certified
- » Joiners colour option: Cream, Charcoal, Copper or Chrome

PANEL COLOUR OPTIONS







 DESCRIPTION
 SIZE (mm)

 Paling A - End Panel
 285W x 1750H

 Paling B - Mid Panel
 285W x 1750H

Watts Commercial Furniture

350a Edgar St Bankstown NSW 2200 PO Box 275 Condell Park 2200 ABN: 54 064 557 893 p: 02 9771 3966 wcf.com.au sales.watts@wcf.com.au accounts.watts@wcf.com.au Watts Commercial Furniture reserves the right to change any or all details without prior notice. Every effort has been made to ensure the information is accurate at the time of printing.



Woven Image - Paling.

Specifications

c .t	
Specifications	
Composition	100% PET (60% post-consumer recycled)
Unit of Sale Net Weight (kg)	3.8
Care Instructions	See Woven Image EchoPanel Care & Cleaning Guide
Test Results	
Fire Test Result	ISO 9705: Group 1, ASTM E84 Unadhered: Class 2 or B, BS EN 13501.1: Classification B - s1, d0
Acoustic Performance Standard Test	AS ISO 354: 2006 (R2016)
Noise Reduction Coeffifficient (NRC)	EchoPanel® 24mm achieves: Direct fix: 0.65, 20mm air gap: 0.75, 50mm air gap: 0.85
Sound Absorption Average (SAA)	EchoPanel® 24mm achieves: Direct fix: 0.63
Weighted Sound Absorption Coefficient (αw) Result	EchoPanel® 24mm achieves: Direct fix: 0.45 (MH), 20mm air gap: 0.50 (MH), 50mm air gap: 0.70 (MH)
Sound Absorption Class	D (Direct fix)
Additional Acoustic Information	Sound Absorption Class result is based on EchoPanel® 24mm. MH = Mid to High Frequency
Colour Fastness to Light Standard Test Method	ISO 105 B02
Colour Fastness Light Rating	6 - 7
VOC Emissions Results	EchoPanel 24mm achieves ASTM D5116: TVOC Emissions Rate: <0.02 mg/m²/hr (7 days), and CDPH Standard Method v1.2: TVOC Emissions Rate: <0.054 mg/m³; Formaldehyde Emissions Rate: $<2\mu$ g/m³
Sustainability Performance Details	EchoPanel achieves GreenTag Certification GreenRate: Level A & Health Rate Platinum, Red List Free, and has an International Living Future Institute Declare Label.